## NSN 5950-01-027-0694

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-027-0694

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.765 inches single mounting facility single center group and 1.797 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.015 inches single mounting facility single center group and 1.047 inches single mounting facility single center group

### Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

#### Input-output Phase Relationship:

Three phase to single phase single component

### **Transformer Winding Connection Type:**

Delta-delta

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

2.281 inches

### **Body Width:**

2.031 inches

### **Body Height:**

1.531 inches

### **Maximum Operating Temp:**

125.0 degrees celsius

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

### **Winding Function And Quantity:**

1 primary single component and 3 secondary single component

### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

375.0 milliamperes dc single component all secondary

### **Winding Operating Voltage:**

120.00 ac volts single component all secondary

### **Special Features:**

Output currents shown as rectified

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

9 tab, solder lug

# NSN 5950-01-027-0694

Power Transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0