## NSN 5950-01-027-3288

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-027-3288

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.000 inches single mounting facility single center group **Frequency Rating:** 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component **Body Length:** 1.500 inches **Body Width:** 1.380 inches **Body Height:** 1.310 inches Inclosure Type: Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.138 inches single group Winding Operating Current: 394.0 milliamperes ac single component all secondary Winding Operating Voltage: 115.00 ac volts single component single primary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 8 pin Shelf Life: N/a Unit Of Measure: ---

## NSN 5950-01-027-3288

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

