

View Online at <https://aerobasegroup.com/nsn/5950-01-027-4913>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches single mounting facility single center group

Mounting Hole Diameter:

0.171 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

0.6 watts single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

7.120 inches

Body Width:

2.500 inches

Body Height:

5.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

2.5 amperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary and 7.50 ac volts single component all secondary and 12.50 ac volts single component all secondary

Terminal Type And Quantity:

43 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0