

View Online at <https://aerobasegroup.com/nsn/5950-01-027-8205>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

48.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

4.500 inches

Body Width:

3.000 inches

Body Height:

3.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

4.1 amperes dc single component single secondary

Winding Operating Voltage:

93.00 ac volts single component 2nd primary and 105.00 ac volts single component 2nd primary and 115.00 ac volts single component 2nd primary and 125.00 ac volts single component 2nd primary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0