NSN 5950-01-028-0300

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-028-0300

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.812 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.281 inches single mounting facility single center group
Mounting Hole Diameter:
0.187 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.125 inches
Body Width:
2.125 inches
Body Height:
2.718 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
2 primary single component and 4 secondary single component
2 primary single component and 4 secondary single component Winding Operating Current:
Winding Operating Current:
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage:
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity:
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity: 15 wire lead
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity: 15 wire lead Shelf Life:
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity: 15 wire lead Shelf Life: N/a
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity: 15 wire lead Shelf Life: N/a
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity: 15 wire lead Shelf Life: N/a Unit Of Measure:
Winding Operating Current: 950.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 28.50 ac volts single component 2nd secondary Terminal Type And Quantity: 15 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: