## NSN 5950-01-028-0953

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-028-0953

| view Online at https://aerobasegroup.com/nsn/5950-01-026-0953             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.843 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.843 inches single mounting facility single center group                 |
| Inductance Rating:  |
| 3.00 millihenries single component single secondary                       |
| Frequency Rating:   |
| 1.0 kilohertz single component  |
| Primary To Secondary Turn Ratio:  |
| 1 to 1 single component   |
| Body Length:  |
| 1.590 inches  |
| Body Width:   |
| 1.453 inches  |
| Body Height:  |
| 1.200 inches  |
| Maximum Operating Temp:   |
| 60.0 degrees celsius  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thread Size:  |
| 0.112 inches single group   |
| Dc Resistance Rating In Ohms:   |
| 0.800 single component single secondary                                   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 4 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5950-01-028-0953

Pulse Transformer - Page 2 of 2



Fiig:

A058b0