NSN 5950-01-028-1748

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-028-1748

Rε	lia	bili	ty	Ind	icate	or:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.5625 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component and internal shield grounded to core single component

Body Length:

18.000 inches

Body Outside Diameter:

6.500 inches

Body Height:

20.750 inches

Overall Diameter:

13.500 inches

Installation For Which Designed:

Outdoor nonportable

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

600.0 amperes ac single component single primary and 21200.0 amperes ac single component single primary

Winding Operating Voltage:

25.00 ac kilovolts single component single primary

Terminal Type And Quantity:

3 threaded stud and 1 standoff, wire lead

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-01-028-1748

Current Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0