# NSN 5950-01-028-1748

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-028-1748

Rε	lia	ıbil	ity	Ind	icato	r:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

8.000 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.500 inches single mounting facility single center group

#### **Mounting Hole Diameter:**

0.5625 inches single group

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component and internal shield grounded to core single component

# **Body Length:**

18.000 inches

#### **Body Outside Diameter:**

6.500 inches

#### **Body Height:**

20.750 inches

# **Overall Diameter:**

13.500 inches

#### **Installation For Which Designed:**

Outdoor nonportable

# **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Flange single group and unthreaded hole single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

## **Winding Operating Current:**

600.0 amperes ac single component single primary and 21200.0 amperes ac single component single primary

## **Winding Operating Voltage:**

25.00 ac kilovolts single component single primary

# **Terminal Type And Quantity:**

3 threaded stud and 1 standoff, wire lead

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-01-028-1748

Current Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0