## NSN 5950-01-028-3413



Power Transformer - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5950-01-028-3413 **Reliability Indicator:** Not established Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to core and brought out to terminal single component **Body Length:** 1.470 inches **Body Width:** 1.380 inches **Body Height:** 1.700 inches **Distance Between Mounting Facility Centers:** 1.125 inches single mounting facility single center group **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 2 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Thready Qty Per Inch (tpi): 40 single group **Thread Size:** 0.112 inches single group **Winding Operating Current:** 800.0 milliamperes dc single component 2nd secondary **Winding Operating Voltage:** 68.00 ac volts single component 1st secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5950-01-028-3413

Power Transformer - Page 2 of 2



Fiig:

A058b0