

View Online at <https://aerobasegroup.com/nsn/5950-01-028-3726>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.843 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.843 inches single mounting facility single center group

Inductance Rating:

3.00 millihenries single component single primary

Primary To Secondary Turn Ratio:

1 to 1 single component

Pulse Repetition Rate:

17.0 kilohertz single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

1.421 inches

Body Width:

1.200 inches

Body Height:

1.590 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

500.0 milliamperes dc single component single primary

Dc Resistance Rating In Ohms:

1.200 single component single primary

Special Features:

Internal shield grounded to core and brought out to terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0