## NSN 5950-01-028-5921

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-028-5921

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.125 inches single mounting facility single center group

### Frequency Rating:

400.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

### **Transformer Winding Connection Type:**

Wye-wye

### Winding Shielding Method:

Internal shield brought out to terminal single component

### **Body Length:**

4.000 inches

### **Body Width:**

2.000 inches

### **Body Height:**

3.750 inches

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

1.3 amperes ac single component 3rd secondary

### **Winding Operating Voltage:**

5.21 ac volts single component 3rd secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

16 tab, solder lug

### Shelf Life:

N/a

# NSN 5950-01-028-5921

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0