# NSN 5950-01-028-6662

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-028-6662

# Reliability Indicator:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

#### Mounting Hole Diameter:

0.174 inches single group

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Maximum Transformer Power Rating:**

12.0 decibels single component

#### Winding Shielding Method:

### Internal shield brought out to terminal single component

Body Length:

2.188 inches

#### Body Width:

1.375 inches

#### **Body Height:**

1.750 inches

#### Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Unthreaded hole single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Winding Operating Voltage:

1.50 ac volts single component single primary

#### **Terminal Type And Quantity:**

7 turret

Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5950-01-028-6662

Power Transformer - Page 2 of 2

**Fiig:** A058b0

