# NSN 5950-01-028-6664

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-028-6664

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.234 inches single mounting facility single center group and 2.266 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Maximum Transformer Power Rating:**

40.0 watts single component

#### **Body Length:**

Between 2.672 inches and 2.704 inches

#### **Body Width:**

Between 2.297 inches and 2.329 inches

#### **Body Height:**

Between 2.984 inches and 3.016 inches

# **Maximum Operating Temp:**

105.0 degrees celsius

# Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### **Features Provided:**

Color coded lead

#### **Thread Size:**

0.164 inches single group

# **Winding Operating Current:**

50.0 milliamperes dc single component 1st secondary

# Winding Power Rating:

12.6 volts-amperes single component 2nd secondary

# **Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

8 wire lead

# NSN 5950-01-028-6664

Power Transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0