

View Online at <https://aerobasegroup.com/nsn/5950-01-028-9560>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.687 inches single mounting facility single center group

Mounting Slot Width:

0.187 inches single group

Frequency Rating:

45.0 hertz single component and 20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

55.0 volt-ampere single component

Body Length:

4.000 inches

Body Width:

3.870 inches

Body Height:

4.375 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 12 secondary single component

Winding Operating Current:

150.0 milliamperes dc single component 1st primary

Winding Operating Voltage:

2.50 ac pounds per hour wet single component 3rd secondary

Special Features:

Two primaries and twelve secondaries

Terminal Type And Quantity:

28 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0