

View Online at <https://aerobasegroup.com/nsn/5950-01-029-3602>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches 1st mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches 1st mounting facility single center group

Frequency Rating:

400.0 hertz single component and 5.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.281 inches

Body Width:

3.656 inches

Body Height:

3.875 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 1st group

Mounting Method:

Threaded stud 3rd group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.250 inches 1st group

Winding Operating Voltage:

59.50 ac volts single component all primary and 63.00 ac volts single component all primary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

9 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0