NSN 5950-01-029-4169

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-029-4169

| Reliability Indicator: |
|--|
| Not established |
| Frequency Rating: |
| 47.0 hertz single component and 63.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to single phase single component and three phase to six phase single component and three phase to three phase single |
| component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 7.750 inches |
| Body Width: |
| 6.250 inches |
| Body Height: |
| 5.450 inches |
| Inclosure Type: |
| Fully enclosed |
| Winding Function And Quantity: |
| 1 primary single component and 7 secondary single component |
| Winding Operating Current: |
| 7.5 amperes dc single component 4th secondary |
| Winding Power Rating: |
| 220.0 volts-amperes single component 2nd secondary |
| Winding Operating Voltage: |
| 44.00 dc volts single component 2nd secondary |
| Special Features: |
| 1 primary winding; 7 secondary windings; secondary voltages are after rectification |
| Terminal Type And Quantity: |
| 27 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |