

View Online at <https://aerobasegroup.com/nsn/5950-01-030-7025>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.200 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

47.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.750 inches

Body Width:

3.380 inches

Body Height:

3.125 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

200.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

8.00 ac volts single component 3rd secondary and 10.20 ac volts single component 3rd secondary and 12.30 ac volts single component 3rd secondary and 14.00 ac volts single component 3rd secondary and 16.10 ac volts single component 3rd secondary

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0