## NSN 5950-01-030-7764

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-030-7764             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.437 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.437 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.188 inches single group   |
| Frequency Rating:   |
| 50.0 hertz single component or 60.0 hertz single component                |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure and core single component           |
| Body Length:  |
| 4.130 inches  |
| Body Width:   |
| 4.130 inches  |
| Body Height:  |
| 3.000 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Winding Function And Quantity:  |
| 2 primary single component and 3 secondary single component               |
| Winding Operating Current:  |
| 850.0 milliamperes dc single component 3rd secondary                      |
| Winding Operating Voltage:  |
| 36.00 ac volts single component 3rd secondary                             |
| Terminal Type And Quantity:   |
| 13 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

. -

A058b0