

View Online at <https://aerobasegroup.com/nsn/5950-01-030-8778>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.750 inches

Body Width:

4.438 inches

Body Height:

6.953 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Power Rating:

560.0 volts-amperes single component single secondary

Winding Operating Voltage:

23.00 ac volts single component single secondary and 28.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret and 3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0