## NSN 5950-01-031-5466

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-031-5466

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.210 inches single mounting facility single center group and 1.270 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.780 inches single mounting facility single center group and 0.840 inches single mounting facility single center group

#### **Overall Width:**

1.710 inches

### **Mounting Hole Diameter:**

0.178 inches single group and 0.198 inches single group

### Frequency Rating:

4.0 kilohertz single component and 5.0 kilohertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

### **Body Length:**

Between 1.590 inches and 1.710 inches

### **Body Width:**

Between 1.210 inches and 1.290 inches

### **Body Height:**

Between 1.220 inches and 1.280 inches

### **Maximum Operating Temp:**

130.0 degrees celsius

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

2 single group

### **Mounting Method:**

Unthreaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 3 secondary single component

### Winding Operating Current:

100.0 milliamperes dc single component 1st secondary

### **Winding Power Rating:**

800.0 milliwatts single component 1st secondary

### **Winding Operating Voltage:**

8.48 ac volts single component 2nd secondary

### **Terminal Type And Quantity:**

12 turret

### Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-01-031-5466

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0