

View Online at <https://aerobasegroup.com/nsn/5950-01-032-0043>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

50.0 hertz single component and 70.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 4.870 inches and 4.880 inches

Body Width:

Between 4.370 inches and 4.380 inches

Body Height:

Between 5.245 inches and 5.255 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 8 secondary single component

Features Provided:

W/rectifier

Winding Operating Current:

700.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

8.00 dc volts single component 2nd secondary

Special Features:

2primary windings; 8secondary windings

Terminal Type And Quantity:

22 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0