## NSN 5950-01-032-0660

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-032-0660

·
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Mounting Hole Diameter:
0.115 inches single group
Inductance Type:
Fixed
Inductance Rating:
170.00 microhenries single component single winding
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Body Length:
1.100 inches
Body Width:
0.640 inches
Body Height:
0.680 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
4 single component
Inclosure Type:
Open
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding
Features Provided:
Tinned wire leads
Winding Operating Current:
500.0 milliamperes ac single component single winding
Dc Resistance Rating In Ohms:
0.250 single component single winding
Terminal Type And Quantity:
8 wire lead
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5950-01-032-0660

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0