## NSN 5950-01-032-0660

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-032-0660

| ·   |
|---|
| Reliability Indicator:  |
| Not established   |
| Hazardous Locations/environmental Protection:                 |
| Vibration resistant   |
| Mounting Hole Diameter:                                       |
| 0.115 inches single group                                     |
| Inductance Type:  |
| Fixed   |
| Inductance Rating:  |
| 170.00 microhenries single component single winding           |
| Frequency Rating:   |
| 380.0 hertz single component and 420.0 hertz single component |
| Body Length:  |
| 1.100 inches  |
| Body Width:   |
| 0.640 inches  |
| Body Height:  |
| 0.680 inches  |
| Maximum Operating Temp:                                       |
| 130.0 degrees celsius   |
| Winding Quantity:   |
| 4 single component  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:                                   |
| 1 single group  |
| Mounting Method:  |
| Unthreaded hole single group                                  |
| Rating Method:  |
| Electrical single component single winding                    |
| Features Provided:  |
| Tinned wire leads   |
| Winding Operating Current:                                    |
| 500.0 milliamperes ac single component single winding         |
| Dc Resistance Rating In Ohms:                                 |
| 0.250 single component single winding                         |
| Terminal Type And Quantity:                                   |
| 8 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

-

## NSN 5950-01-032-0660

Reactor - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A058b0