

View Online at <https://aerobasegroup.com/nsn/5950-01-032-1166>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.687 inches single mounting facility single center group and 3.812 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.937 inches single mounting facility single center group and 3.062 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

Between 4.437 inches and 4.562 inches

**Body Width:**

Between 3.687 inches and 3.812 inches

**Body Height:**

6.000 inches

**Inclosure Type:**

Partially enclosed, half shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 5 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

650.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

320.00 ac volts single component 2nd secondary

**Special Features:**

2 primary windings; 5 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0