

View Online at <https://aerobasegroup.com/nsn/5950-01-032-1168>

Reliability Indicator:

Not established

Overall Length:

6.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.641 inches single mounting facility single center group and 3.735 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.953 inches single mounting facility single center group and 3.047 inches single mounting facility single center group

Overall Height:

Between 3.875 inches and 4.000 inches

Overall Width:

Between 4.563 inches and 4.688 inches

Frequency Rating:

45.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

2.5 amperes ac single component single secondary

Winding Operating Voltage:

460.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0