

View Online at <https://aerobasegroup.com/nsn/5950-01-032-1905>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.370 inches single mounting facility single center group and 1.380 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.645 inches single mounting facility single center group and 0.655 inches single mounting facility single center group

Mounting Hole Diameter:

0.123 inches single group and 0.129 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.675 inches and 1.685 inches

Body Width:

Between 0.935 inches and 0.945 inches

Body Height:

Between 0.835 inches and 0.845 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 milliamperes ac single component single primary

Winding Operating Voltage:

3.70 ac volts single component single secondary and 10.10 ac volts single component single secondary and 13.80 ac volts single component single secondary

Terminal Type And Quantity:

5 pin and 2 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0