

View Online at <https://aerobasegroup.com/nsn/5950-01-033-5663>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.187 inches single mounting facility single center group

Mounting Hole Diameter:

0.140 inches single group and 0.144 inches single group

Frequency Rating:

1.2 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.125 inches

Body Width:

0.870 inches

Body Height:

1.680 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

9.0 amperes ac single component single secondary

Winding Operating Voltage:

58.50 ac volts single component single secondary

Special Features:

Center tap common to both primary windings

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0