## NSN 5950-01-034-1922

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-034-1922

•
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.438 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
3.375 inches
Body Width:
2.813 inches
Body Height:
3.125 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
30.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
37.10 ac volts single component 2nd secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-034-1922

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0