

View Online at <https://aerobasegroup.com/nsn/5950-01-034-1923>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.937 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Maximum Transformer Power Rating:

457.4 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.250 inches

Body Width:

3.560 inches

Body Height:

1.500 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

560.0 milliamperes dc single component 2nd secondary

Winding Power Rating:

376.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

4.30 dc volts single component 3rd secondary

Special Features:

One primary winding; five secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

19 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A058b0