

View Online at <https://aerobasegroup.com/nsn/5950-01-034-4096>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.750 inches

Body Width:

1.200 inches

Body Height:

0.875 inches

Maximum Operating Temp:

75.0 degrees celsius

Distance Between Mounting Facility Centers:

1.375 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 milliamperes dc single component single secondary

Winding Operating Voltage:

35.00 ac pounds per hour wet single component single secondary

Special Features:

Secondary to work into full wave rectifier w/ capacitive input filter, 24 voltage dc under these conditions

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0