## NSN 5950-01-035-5928

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-035-5928

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.938 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.875 inches single mounting facility single center group

### **Overall Height:**

Between 1.720 inches and 1.750 inches

### Frequency Rating:

400.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

### **Transformer Winding Connection Type:**

Wye-delta

### **Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

### **Body Length:**

Between 2.280 inches and 2.310 inches

### **Body Width:**

Between 2.220 inches and 2.250 inches

### **Body Height:**

Between 1.470 inches and 1.500 inches

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

#### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

200.0 milliamperes ac single component single primary input

### **Winding Operating Voltage:**

120.00 ac volts single component single primary input

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

14 turret

### Shelf Life:

N/a

# NSN 5950-01-035-5928

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0