

View Online at <https://aerobasegroup.com/nsn/5950-01-035-6219>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.062 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 6.687 inches and 6.812 inches

**Body Width:**

Between 5.812 inches and 5.937 inches

**Body Height:**

Between 4.937 inches and 5.125 inches

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 9 secondary single component

**Thread Size:**

0.312 inches single group

**Winding Operating Current:**

220.0 milliamperes ac single component 4th secondary

**Winding Operating Voltage:**

23.00 ac volts single component 4th secondary

**Special Features:**

1primary winding; 9secondary windings

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

19 solder stud and 2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0