

View Online at <https://aerobasegroup.com/nsn/5950-01-035-6219>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.062 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 6.687 inches and 6.812 inches

Body Width:

Between 5.812 inches and 5.937 inches

Body Height:

Between 4.937 inches and 5.125 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Thread Size:

0.312 inches single group

Winding Operating Current:

220.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

23.00 ac volts single component 4th secondary

Special Features:

1primary winding; 9secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

19 solder stud and 2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0