

View Online at <https://aerobasegroup.com/nsn/5950-01-036-0138>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facili type 2nd center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facili type 2nd center group

Frequency Rating:

47.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

5.630 inches

Body Width:

4.500 inches

Body Height:

5.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

8 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Features Provided:

Color coded lead

Thread Size:

0.190 inches all groupings

Winding Operating Current:

3.8 amperes dc single component 3rd secondary

Winding Operating Voltage:

9.00 dc volts single component 2nd secondary and 11.00 dc volts single component 2nd secondary

Special Features:

1primary; 5 secondary windings

Thread Series Designator:

Unf all groupings

Terminal Type And Quantity:

16 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0