

View Online at <https://aerobasegroup.com/nsn/5950-01-036-0995>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.940 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group

**Mounting Slot Width:**

0.340 inches single group

**Frequency Rating:**

48.0 hertz single component and 440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

60.7 volt-ampere single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

3.620 inches

**Body Width:**

3.000 inches

**Body Height:**

2.520 inches

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

2 primary single component and 4 secondary single component

**Winding Operating Current:**

550.0 milliamperes ac single component 2nd secondary

**Winding Power Rating:**

44.5 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

30.00 ac volts single component 1st secondary

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0