

View Online at <https://aerobasegroup.com/nsn/5950-01-036-6137>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.010 inches single mounting facility single center group and 4.111 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.260 inches single mounting facility single center group and 3.360 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 4.940 inches and 5.063 inches

Body Width:

Between 4.190 inches and 4.310 inches

Body Height:

Between 6.620 inches and 6.813 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

200.0 milliamperes dc single component single secondary and 450.0 milliamperes dc single component single secondary and 500.0 milliamperes dc single component single secondary

Winding Operating Voltage:

450.00 ac volts single component single secondary and 1.20 ac kilovolts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0