NSN 5950-01-037-9758

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-037-9758

To Length:

To Width:

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel |
| 2.187 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel |
| 1.781 inches single mounting facility single center group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to single phase single component |
| Transformer Winding Connection Type: |
| Wye-wye |
| Body Length: |
| 3.600 inches |
| Body Width: |
| 2.160 inches |
| Body Height: |
| 3.000 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 740.0 milliamperes ac single component single primary |
| Winding Operating Voltage: |
| 21.30 ac volts single component 3rd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 16 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5950-01-037-9758

Power Transformer - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A058b0