

View Online at <https://aerobasegroup.com/nsn/5950-01-039-2259>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

4.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.410 inches single mounting facility single center group and 3.470 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.720 inches single mounting facility single center group and 2.780 inches single mounting facility single center group

**Overall Height:**

4.170 inches

**Frequency Rating:**

47.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Width:**

3.450 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 5 secondary single component

**Features Provided:**

Color coded lead

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

200.0 milliamperes ac single component 3rd secondary

**Winding Power Rating:**

8.0 volts-amperes single component 4th secondary

**Winding Operating Voltage:**

90.50 ac volts single component 3rd secondary

**Special Features:**

2 primary windings and 5 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 tab, solder lug and 11 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0