

View Online at <https://aerobasegroup.com/nsn/5950-01-039-6270>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.875 inches

Body Width:

3.562 inches

Body Height:

3.062 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

10.0 milliamperes ac single component single secondary

Winding Power Rating:

12.75 volts-amperes single component single secondary

Winding Operating Voltage:

1275.00 ac volts single component single secondary

Special Features:

Warning marking "danger 1275 volts" in 1/2 high white on red background near terminals 3-4

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 threaded stud and 2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0