

View Online at <https://aerobasegroup.com/nsn/5950-01-039-7155>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

52.0 millimeters single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

41.0 millimeters single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

51.2 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

65.0 millimeters

Body Width:

63.0 millimeters

Body Height:

90.0 millimeters

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

550.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

9.50 ac volts single component 2nd secondary

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0