NSN 5950-01-040-4130

Power Transformer - Page 1 of 2



sn/5950-01-040-4130

| View Online at https://aerobasegroup.com/nsn/5950-01-040-4130 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.688 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.438 inches single mounting facility single center group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |

2.312 inches **Body Width:** 2.062 inches **Body Height:** 3.125 inches **Inclosure Type:** Hermetically sealed

4 single group **Mounting Method:**

32 single group **Thread Size:**

Mounting Facility Quantity:

Threaded stud single group

Thready Qty Per Inch (tpi):

0.138 inches single group **Winding Operating Current:**

Winding Operating Voltage:

Thread Series Designator:

Terminal Type And Quantity:

Unc single group

Unit Of Measure:

7 solder stud Shelf Life:

N/a

Winding Function And Quantity:

1 primary single component and 1 secondary single component

1.0 amperes ac single component single secondary

6.30 ac volts single component single secondary

NSN 5950-01-040-4130

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0