

View Online at <https://aerobasegroup.com/nsn/5950-01-040-6294>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.312 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.688 inches single mounting facility single center group

**Inductance Type:**

Fixed

**Inductance Rating:**

3.00 millihenries single component single winding

**Frequency Rating:**

360.0 hertz single component

**Body Length:**

4.312 inches

**Body Width:**

3.688 inches

**Body Height:**

4.500 inches

**End Application:**

Ticonderoga class cg (47); spruance class dd (963); wasp class lhd; radar, series an/sps-4 (v); forrestal class cv; virginia class cgn (41); whidbey island class lsd; oliver perry class ffg; nimitz class cvn; kidd class ddg

**Winding Quantity:**

1 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Electrical single component single winding

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

22.0 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

0.100 single component single winding

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0