

View Online at <https://aerobasegroup.com/nsn/5950-01-040-6294>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

3.00 millihenries single component single winding

Frequency Rating:

360.0 hertz single component

Body Length:

4.312 inches

Body Width:

3.688 inches

Body Height:

4.500 inches

End Application:

Ticonderoga class cg (47); spruance class dd (963); wasp class lhd; radar, series an/sps-4 (v); forrestal class cv; virginia class cgn (41); whidbey island class lsd; oliver perry class ffg; nimitz class cvn; kidd class ddg

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

22.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.100 single component single winding

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0