NSN 5950-01-041-8322

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-041-8322

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

58.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Body Length:

2.000 inches

Body Width:

2.000 inches

Body Height:

2.210 inches

End Application:

An/alq-119

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

40.0 amperes dc single component single secondary

Winding Power Rating:

300.0 volts-amperes single component single primary

Winding Operating Voltage:

279.00 ac volts single component single primary

Special Features:

Primary 279vdc, secondary 22.5v peak

Thread Series Designator:

Unc single group

NSN 5950-01-041-8322

Power Transformer - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

3 threaded stud and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0