

View Online at <https://aerobasegroup.com/nsn/5950-01-043-1983>

Reliability Indicator:

Not established

Overall Length:

Between 1.719 inches and 1.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.234 inches single mounting facility single center group and 1.266 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.046 inches single mounting facility single center group and 1.078 inches single mounting facility single center group

Overall Height:

Between 2.626 inches and 2.874 inches

Overall Width:

Between 1.469 inches and 1.531 inches

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

200.0 milliamperes ac single component single secondary

Winding Power Rating:

5.0 volts-amperes single component single secondary

Winding Operating Voltage:

25.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0