

View Online at <https://aerobasegroup.com/nsn/5950-01-043-3165>

Reliability Indicator:

Not established

Overall Length:

3.320 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

360.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Width:

2.120 inches

Body Height:

1.560 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.6 amperes ac single component 4th secondary

Winding Operating Voltage:

216.00 ac volts single component single primary and 264.00 ac volts single component single primary

Special Features:

1 primary, 6 secondary windings; secondary 6 has multiple taps providing voltages with varying currents in milliamperes

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0