

View Online at <https://aerobasegroup.com/nsn/5950-01-044-4048>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

5.000 inches

Body Width:

3.000 inches

Body Height:

1.380 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

710.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

30.50 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0