NSN 5950-01-044-4495

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-044-4495

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 4.100 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.690 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.130 inches single mounting facility single center group |
| Overall Width: |
| 3.440 inches |
| Mounting Slot Width: |
| 0.156 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Transformer Winding Connection Type: |
| Delta-wye |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Width: |
| 3.190 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 5 secondary single component |
| Winding Operating Current: |
| 2.2 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 199.00 ac pounds per hour wet single component single primary |
| Special Features: |
| 1 primary winding; 5 secondary windings |
| Terminal Type And Quantity: |
| 18 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-01-044-4495

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0