

View Online at <https://aerobasegroup.com/nsn/5950-01-045-0231>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group and 2.540 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.830 inches single mounting facility single center group and 1.870 inches single mounting facility single center group

Overall Height:

Between 5.010 inches and 5.240 inches

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 3.110 inches and 3.270 inches

Body Width:

Between 2.440 inches and 2.520 inches

Body Height:

Between 4.560 inches and 4.730 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

2.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0