NSN 5950-01-045-7289

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-045-7289

Note established Turn Quantity: 45 single component single winding Inductance Rating: 20.90 microhenries single component single winding and 23.10 microhenries single component single winding Coli Form Type: Hollow single component Core Construction: Solid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Height: 0.375 inches Body Height: 0.375 inches Body Height: 0.376 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Oc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
Turn Quantity: 45 single component single winding Inductance Rating: 20.90 microhenries single component single winding and 23.10 microhenries single component single winding Coil Form Type: Hollow single component Core Construction: Solid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Electrical single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	•
45 single component single winding Inductance Rating: 20.90 microhenries single component single winding and 23.10 microhenries single component single winding Coil Form Type: Hollow single component Core Construction: Sülid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Electrical single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Inductance Rating: 20.90 microhenries single component single winding and 23.10 microhenries single component single winding Coil Form Type: Hollow single component Core Construction: Sülid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.376 inches Body Height: 0.376 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
20.90 microhenries single component single winding and 23.10 microhenries single component single winding Coll Form Type: Hollow single component Core Construction: SOlid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Electrical single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding De Resistance Rating in Ohms: 2.200 single component single winding Quality Factor: 5 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Sheff Life: N/a	
Coll Form Type: Hollow single component Core Construction: SOlid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Hollow single component Core Construction: Sülid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes de single component single winding De Resistance Rating In Ohms: 2.200 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Core Construction: Solid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Oc Resistance Rating In Ohms: 2.200 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Solid single component Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding De Resistance Rating in Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Adjustment Device Drive Type: Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Hex socket single component Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Body Length: 0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
0.375 inches Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal Single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Body Width: 0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal Single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
0.375 inches Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Body Height: 0.340 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Winding Conductor Size: 0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	-
0.00198 inches american wire gage single component single winding Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Winding Operating Current: 48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	-
48.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Dc Resistance Rating In Ohms: 2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
2.200 single component single winding Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Quality Factor: 55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	-
55 single component single winding and 60 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Adjustment Method And Quantity: 1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
1 adjustable core single component Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Terminal Type And Quantity: 2 pin Shelf Life: N/a	
2 pin Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Unit Of Medoufe.	
	
Demilitarization:	Demilitarization:

No

NSN 5950-01-045-7289Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0